Heavy Duty Flatbed Trailer

FLATBED

Optional Omaha Orange, Semi-style Jacks & Oak Flooring

Optional Center Flip-over Beavertail

Optional Angle Iron Beavertail

Optional (3) Flip-over Ramps & Rumber Flooring

Optional Gorilla Ramps

Optional Tongue Mounted Toolbox

TRAILERS B-B BEHNKE ENTERPRISES, INC.

DEXTER AXLE

Manufactured by:

Behnke Enterprises, Inc. · 800 Ninth Ave. NW · Farley, IA 52046 · Ph. (563)744-3246·Fax (563)744-9066
www.behnkeenterprises.com

Heavy Duty Flatbed Trailer

TRAILERS B-B BEHNKE ENTERPRISES, INC.

Pulltype

14-40,000 lb., No Beavertail		
Model	**Length**	**Width**
FB8X16PT	16'	8' 6"
FB8X18PT	18'	8' 6"
FB8X20PT	20'	8' 6"
FB8X22PT	22'	8' 6"
FB8X24PT	24'	8' 6"

14-40,000 lb., With Beavertail		
Model	**Length**	**Width**
FB8X21PT	16' + 5' Tail	8' 6"
FB8X23PT	18' + 5' Tail	8' 6"
FB8X25PT	20' + 5' Tail	8' 6"
FB8X27PT	22' + 5' Tail	8' 6"
FB8X29PT	24' + 5' Tail	8' 6"
5' Flip-over Ramps, Spring Assist		

Gooseneck

14-30,000 lb., No Beavertail		
Model	**Length**	**Width**
FB8X16GN	16'	8' 6"
FB8X18GN	18'	8' 6"
FB8X20GN	20'	8' 6"
FB8X22GN	22'	8' 6"
FB8X24GN	24'	8' 6"
FB8X26GN	26'	8' 6"
FB8X28GN	28'	8' 6"

14-30,000 lb., With Beavertail		
Model	**Length**	**Width**
FB8X21GN	16' + 5' Tail	8' 6"
FB8X23GN	18' + 5' Tail	8' 6"
FB8X25GN	20' + 5' Tail	8' 6"
FB8X27GN	22' + 5' Tail	8' 6"
FB8X29GN	24' + 5' Tail	8' 6"
FB8X31GN	26' + 5' Tail	8' 6"
FB8X33GN	28' + 5' Tail	8' 6"
FB8X35GN	30' + 5' Tail	8' 6"
5' Flip-over Ramps, Spring Assist		

Standard Axle Size

(2) 7,000 lb. Dexter E-Z Lube Axles with Electric and Forward Self-Adjusting Brakes	
(4) ST235-80R-16E Radial Tire with White 8-Hole Wheel	
Axle Upgrades	***Tire and Wheel***
(2) 8,000 lb. oil bath axle	Single 215/75R-17.5H tire and wheel
(2) 10,000 lb. general duty oil bath	Dual ST235-80R-16E tire and wheel
(2) 10,000 lb. heavy duty oil bath	Dual ST235-80R-16E tire and wheel
(2) 10,000 lb. heavy duty oil bath	Single 215-75R-17.5 tire and wheel
(2) 12,000 lb. heavy duty oil bath	Dual ST235-80R-16E tire and wheel
(2) 15,000 lb. heavy duty oil bath	Dual 215/75R-17.5H tire and wheel
(2) 20,000 lb. Air Brake	Dual 235/75R-17.5H tire and wheel

Standard Equipment

Frame (14 GVW)	12" 14.5 Lb. I-Beam	**Frame (24 GVW)**	12 x 22 Lb. I-Beam
Frame (16 GVW)	12" 14 Lb. I-Beam	**Frame (30 GVW)**	12 x 22 Lb. I-Beam
Frame (20 GVW)	12" 19 Lb. I-Beam	**Frame (40 GVW)**	12 x 26 Lb. I-Beam

Ramps	No Tail - No Ramp; With Tail - 5' Flip-over Ramps, Spring Assist
Hitch	Pintle, 2 5/16" Adjustable Coupler or 2 5/16" Adjustable Gooseneck
Floor	2 x 8 Treated Wood Floor
Tool Box	(1) 12" x 18" x 48" Toolbox
Jack	(1) 10,000 lb. Heavy Duty Spring Loaded Jack

Optional Beavertail: Angle iron; Center flip-up

Optional Gorilla Ramps

Standard Equipment

(2) 3/8 Safety Chains
Rub Rail & Stake Pockets
12-Volt Breakaway Kit
Modular Wire Harness
Rubber Mounted LED Lights
Mud Flaps
Reflector Tape
Zinc Primer and Powder Coat Finish
-- Standard: Black, Red, Blue, Gray, Yellowstone

Manufactured by: Behnke Enterprises, Inc. ▪ 800 Ninth Ave. NW, Farley, IA 52046 ▪ Ph. (563)744-3246 ▪ Fax (563)744-9066

www.behnkeenterprises.com

DEXTER AXLE