



Model	Axle Description	Tire Size	GAWR	GVWR
CUSHION TILT BED 14K				
20x83" CT14	2 - 7000# Dexter	ST235/80R/16 LRE	7000#	14000#
22x83" CT14	2 - Electric Brakes Nev-R-Adjust			
24x83" CT14	E-Z Lube - 1/2 Cambered			

Standard Equipment

- Coupler: 2 5/16" Forged Adjustable 5/Position
- Jack: 10000# Drop Leg
- Fenders: HD Diamond Plate w/Drop
- Floor: 2" Treated Pine
- Brake: Electric All Wheel
- Break Away Unit w/Charger
- Stake Pockets
- Spare Rack
- Flush Floor
- Inverted Dovetail
- Cushion Shock Absorber w/Control Valve
- 4" Drop Axle
- Sealed Flush Mount LED Lights
- Colors: Refer to Chart
- **Note:** 20' Trailer Has 4' Stationary Deck w/16' Tilting Deck
- **Note:** 22' Trailer Has 4' Stationary Deck w/18' Tilting Deck
- **Note:** 24' Trailer Has 6' Stationary Deck w/18' Tilting Deck
- **Not Recommended For Heavy Loads On Rear Of Trailer.**
- **Load Should Not Exceed 2' Behind Rear Axle.**

Frame Structure

- Frame: 6" Channel
- Deck Frame: 6" Channel
- Crossmembers: 3" Channel 16" OC
- Tongue: 6" Channel

Options

- Gooseneck w/10" I-Beam Neck & 4" Channel Truss
- Weld-On D-Rings 5/8"
- Spare ST235/80R/16 LRE on 8-Hole
- **Other Options Available**