

	7 x 29	7 x 31	7 x 33
Model #	H8220EX-GN-100	H8222EX-GN-100	H8224EX-GN-100
CAPACITIES			
GVWR (lbs)		9900	
GAWR (lbs/axle)		5200	
Curb Weight	3500		4220
Payload	6400		5680
CHASSIS			
Frame		6" Steel Channel	
Tongue		10" Flange, 12 lb/ft I-Beam, Gooseneck	
Crossmembers		3" Steel Channel, 16" On-Center	
Coupler		2-5/16" Adjustable Gooseneck	
Tongue Jack		Dual 12K Drop Leg	
Bulkhead		HD Tube	
Dovetail		Reverse Taper Cut	
Fenders		Double Break Tread Plate	
Axle		(2) 5200 lb. Spring Brake	
Hubs		Easy Lube	
Tires		ST225/75R15D 8-PR	
Wheels		15", 6-Hole Steel	
Exterior Finish		Industrial Grade Polymer Finish	
Decking		2" Pressure Treated Pine, Board Retainers	
Tie Downs		Banjo Tie-Downs, Stake Pockets	
Exterior Storage		Integrated Gooseneck Tool and Pump Box, Spare Tire Carrier, Recessed In Neck	
Wiring		Sealed Wiring Harness	
Exterior Lights		Full LED, DOT Compliant	
Hydraulic Components		Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
Warranty		Limited 3-Year Warranty	
DIMENSIONS			
Overall Length	340	364	388

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

HHSOEXGN10,HHSOEXGN14,HHSOEXGN16,HHSOEXGN7,HHSOEX10,HHSOEX14,HHSOEX16,HHSOEX7,HHSOMX7,HHSOMX10,HHSOMX14,HHSOEXL10,HH: **STEEL E**

	7 x 27	7 x 29	7 x 31	7 x 33
Model #	H8218EX-GN-140	H8220EX-GN-140	H8222EX-GN-140	H8224EX-GN-140
CAPACITIES				
GVWR (lbs)			14000	
GAWR (lbs/axle)			7000	
Curb Weight		4330	3930	4500
Payload		9670	10070	9500
CHASSIS				
Frame		6" Steel Channel		
Tongue		10" Flange, 12 lb/ft I-Beam, Gooseneck		
Crossmembers		3" Steel Channel, 16" On-Center		
Coupler		2-5/16" Adjustable Gooseneck		
Tongue Jack		Dual 12K, 2-Speed Landing Gear		
Dovetail		Reverse Taper Cut		
Fenders		Double Break Tread Plate		
Axle		(2) 7000 lb. Slipper Spring Brake		
Hubs		Easy Lube		
Tires		ST235/80R16E 10-PR		
Wheels		16", 8-Hole Steel		
Exterior Finish		Industrial Grade Polymer Finish		
Decking		2" Pressure Treated Pine, Board Retainers		
Tie Downs		Banjo Tie-Downs, Stake Pockets		
Exterior Storage		Integrated Gooseneck Tool and Pump Box		
Wiring		Sealed Wiring Harness		
Exterior Lights		Full LED, DOT Compliant		
Hydraulic Components		Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
Warranty		Limited 3-Year Warranty		
DIMENSIONS				
Overall Length	316	340	364	388

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

7 x 33	
Model #	H8224EX-GN-160
CAPACITIES	
GVWR (lbs)	16000
GAWR (lbs/axle)	8000
Curb Weight	4560
Payload	11440
CHASSIS	
Frame	8" Steel Channel
Tongue	10" Flange, 12 lb/ft I-Beam, Gooseneck
Crossmembers	3" Steel Channel, 16" On-Center
Coupler	2-5/16" Adjustable Gooseneck
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Dovetail	Reverse Taper Cut
Fenders	Double Break Tread Plate
Axle	(2) 8000 lb. Slipper Spring Brake
Hubs	Oil Bath
Tires	215/75R17.5J 18-PR
Wheels	17.5", 8-Hole Steel
Exterior Finish	Industrial Grade Polymer Finish
Decking	2" Pressure Treated Pine, Board Retainers
Tie Downs	Banjo Tie-Downs
Exterior Storage	Spare Tire Carrier, Recessed In Neck, Tongue Mounted Lockable Battery and Pump Box
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead
Warranty	Limited 3-Year Warranty
DIMENSIONS	
Overall Length	388

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

7 x 29	
Model #	H8220EX-GN-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
Curb Weight	3650
Payload	3350
CHASSIS	
Frame	6" Steel Channel
Tongue	10" Flange, 12 lb/ft I-Beam, Gooseneck
Crossmembers	3" Steel Channel, 16" On-Center
Coupler	2-5/16" Adjustable Gooseneck
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Dovetail	Reverse Taper Cut
Fenders	Double Break Tread Plate
Axle	(2) 3500 lb. Slipper Spring Brake
Hubs	Easy Lube
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Steel
Exterior Finish	Industrial Grade Polymer Finish
Decking	2" Pressure Treated Pine, Board Retainers
Tie Downs	Banjo Tie-Downs, Stake Pockets
Exterior Storage	Spare Tire Carrier, Recessed In Neck, Tongue Mounted Lockable Battery and Pump Box
Wiring	Sealed Wiring Harness
Exterior Lights	Full LED, DOT Compliant
Hydraulic Components	Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead
Warranty	Limited 3-Year Warranty
DIMENSIONS	
Overall Length	340

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 23	7 x 25	7 x 27	7 x 29
Model #	HEXL8218-BP-100	HEXL8220-BP-100	HEXL8222-BP-100	HEXL8224-BP-100
CAPACITIES				
GVWR (lbs)			9900	
GAWR (lbs/axle)			5200	
Curb Weight		2650	3065	3110
Payload		7250	6835	6790
CHASSIS				
Frame		6" Steel Channel		
Tongue		5" Steel Channel, Fully Wrapped		
Crossmembers		3" Steel Channel, 16" On-Center		
Coupler		2-5/16" A-Frame, Posi-Lock		
Tongue Jack		7K Drop Leg, Set-Back		
Bulkhead		HD Tube		
Dovetail		Reverse Taper Cut		
Fenders		Double Break Tread Plate		
Axle		(2) 5200 lb. Drop Spring Brake		
Hubs		Easy Lube		
Tires		ST225/75R15D 8-PR		
Wheels		15", 6-Hole Steel		
Exterior Finish		Industrial Grade Polymer Finish		
Decking		2" Pressure Treated Pine, Board Retainers		
Tie Downs		Banjo Tie-Downs, Stake Pockets		
Exterior Storage		Tongue Mounted Lockable Battery and Pump Box		
Wiring		Sealed Wiring Harness		
Exterior Lights		Full LED, DOT Compliant		
Hydraulic Components		Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead		
Warranty		Limited 3-Year Warranty		
DIMENSIONS				
Overall Length	276	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

HHSOEXGN10,HHSOEXGN14,HHSOEXGN16,HHSOEXGN7,HHSOEX10,HHSOEX14,HHSOEX16,HHSOEX7,HHSOMX7,HHSOMX10,HHSOMX14,HHSOEXL10,HH:
STEEL I

	7 x 25	7 x 27	7 x 29
Model #	HEXL8220-BP-140	HEXL8222-BP-140	HEXL8224-BP-140
CAPACITIES			
GVWR (lbs)		14000	
GAWR (lbs/axle)		7000	
Curb Weight	3050	3200	3450
Payload	10950	10800	10550
CHASSIS			
Frame		6" Steel Channel	
Tongue		6" Steel Channel, Fully Wrapped	
Crossmembers		3" Steel Channel, 16" On-Center	
Coupler		2-5/16" Adjustable, Posi-Lock	
Tongue Jack		12K Drop Leg, Set-Back	
Bulkhead		Custom Formed	
Dovetail		Reverse Taper Cut	
Fenders		Double Break Tread Plate	
Axle		(2) 7000 lb. Drop Spring Brake	
Hubs		Easy Lube	
Tires		ST235/80R16E 10-PR	
Wheels		16", 8-Hole Steel	
Exterior Finish		Industrial Grade Polymer Finish	
Decking		2" Pressure Treated Pine, Board Retainers	
Tie Downs		Banjo Tie-Downs, Stake Pockets	
Exterior Storage		Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox	
Wiring		Sealed Wiring Harness	
Exterior Lights		Full LED, DOT Compliant	
Hydraulic Components		Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
Warranty		Limited 3-Year Warranty	
DIMENSIONS			
Overall Length	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

HHSOEXGN10,HHSOEXGN14,HHSOEXGN16,HHSOEXGN7,HHSOEX10,HHSOEX14,HHSOEX16,HHSOEX7,HHSOMX7,HHSOMX10,HHSOMX14,HHSOEXL10,HH: **STE**

	7 x 23	7 x 25	7 x 27	7 x 29
Model #	HEX8218-BP-100	HEX8220-BP-100	HEX8222-BP-100	HEX8224-BP-100
CAPACITIES				
GVWR (lbs)			9900	
GAWR (lbs/axle)			5200	
Curb Weight	2430	2620	2420	3030
Payload	7470	7280	7480	6870
CHASSIS				
Frame	6" Steel Channel			
Tongue	5" Steel Channel, Fully Wrapped			
Crossmembers	3" Steel Channel, 16" On-Center			
Coupler	2-5/16" A-Frame, Posi-Lock			
Tongue Jack	7K Drop Leg, Set-Back			
Bulkhead	Custom Formed			
Dovetail	Reverse Taper Cut			
Fenders	Double Break Tread Plate			
Axle	(2) 5200 lb. Spring Brake			
Hubs	Easy Lube			
Tires	ST225/75R15D 8-PR			
Wheels	15", 6-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Board End Caps			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated			
Warranty	Limited 3-Year Warranty			
DIMENSIONS				
Overall Length	276	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 28	7 x 23	7 x 25	7 x 29
Model #	HEX8222-BP-140	HEX8218-BP-140	HEX8220-BP-140	HEX8224-BP-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	3180	2740	2870	3390
Payload	10820	11260	11130	10610
CHASSIS				
Frame	6" Steel Channel			
Tongue	6" Steel Channel, Fully Wrapped			
Crossmembers	3" Steel Channel, 16" On-Center			
Coupler	2-5/16" Adjustable, Posi-Lock			
Tongue Jack	12K Drop Leg, Set-Back			
Bulkhead	HD Tube			
Dovetail	Reverse Taper Cut			
Fenders	Double Break Tread Plate			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Board End Caps			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead			
Warranty	Limited 3-Year Warranty			
DIMENSIONS				
Overall Length		276	300	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 25	7 x 27	7 x 29
Model #	HEX8220-BP-160	HEX8222-BP-160	HEX8224-BP-160
CAPACITIES			
GVWR (lbs)		16000	
GAWR (lbs/axle)		8000	
Curb Weight	3380		4080
Payload	12620		11920
CHASSIS			
Frame		8" Steel Channel	
Tongue		6" Steel Channel, Fully Wrapped	
Crossmembers		3" Steel Channel, 16" On-Center	
Coupler		2 5/16" Adjustable Channel Mount, Demco EZ Latch	
Tongue Jack		12K Drop Leg, Set-Back	
Bulkhead		Custom Formed	
Dovetail		Reverse Taper Cut	
Fenders		Double Break Tread Plate	
Axle		(2) 8000 lb. Slipper Spring Brake	
Hubs		Oil Bath	
Tires		215/75R17.5J 18-PR	
Wheels		17.5", 8-Hole Steel	
Exterior Finish		Industrial Grade Polymer Finish	
Decking		2" Pressure Treated Pine, Board Retainers	
Tie Downs		Banjo Tie-Downs, Stake Pockets	
Exterior Storage		Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box	
Wiring		Sealed Wiring Harness	
Exterior Lights		Full LED, DOT Compliant	
Hydraulic Components		Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
Warranty		Limited 3-Year Warranty	
DIMENSIONS			
Overall Length	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 23	7 x 25
Model #	HEX8218-BP-070	HEX8220-BP-070
CAPACITIES		
GVWR (lbs)		7000
GAWR (lbs/axle)		3500
Curb Weight	1960	1990
Payload	5040	5010
CHASSIS		
Frame	5" Steel Channel	
Tongue	5" Steel Channel, Fully Wrapped	
Crossmembers	3" Steel Channel	
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue Jack	7K Drop Leg, Set-Back	
Bulkhead	Custom Formed	
Dovetail	Reverse Taper Cut	
Fenders	Double Break Tread Plate	
Axle	(2) 3500 lb. Spring Brake	
Hubs	Easy Lube	
Tires	ST205/75R15C 6-PR	
Wheels	15", 5-Hole Steel	
Exterior Finish	Industrial Grade Polymer Finish	
Decking	2" Pressure Treated Pine, Board End Caps	
Tie Downs	Banjo Tie-Downs, Stake Pockets	
Exterior Storage	Spare Tire Carrier, Tongue Mounted Lockable Battery and Pump Box, Tongue Mounted Toolbox	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Hydraulic Components	12 Volt Hydraulic Pump, Hydraulic Tilt Cylinder (EX) Electric Power Operated, Push Button Control with 15' Lead	
Warranty	Limited 3-Year Warranty	
DIMENSIONS		
Overall Length	276	300

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

HHSOEXGN10,HHSOEXGN14,HHSOEXGN16,HHSOEXGN7,HHSOEX10,HHSOEX14,HHSOEX16,HHSOEX7,HHSOMX7,HHSOMX10,HHSOMX14,HHSOEXL10,HH:
STEEL

	7 x 23	7 x 25	7 x 27
Model #	H8218MXL-100	H8220MXL-100	H8222MXL-100
CAPACITIES			
GVWR (lbs)		9900	
GAWR (lbs/axle)		5200	
Curb Weight	2390	2550	2810
Payload	7510	7350	7090
CHASSIS			
Frame		6" Steel Channel	
Tongue		5" Steel Channel, Fully Wrapped	
Crossmembers		3" Steel Channel, 16" On-Center	
Coupler		2-5/16" A-Frame, Posi-Lock	
Tongue Jack		7K Drop Leg, Set-Back	
Bulkhead		HD Tube	
Dovetail		Reverse Taper Cut	
Fenders		Double Break Tread Plate	
Axle		(2) 5200 lb. Drop Spring Brake	
Hubs		Easy Lube	
Tires		ST225/75R15D 8-PR	
Wheels		15", 6-Hole Steel	
Exterior Finish		Industrial Grade Polymer Finish	
Decking		2" Pressure Treated Pine, Board Retainers	
Tie Downs		Banjo Tie-Downs, Stake Pockets	
Exterior Storage		Spare Tire Carrier	
Wiring		Sealed Wiring Harness	
Exterior Lights		Full LED, DOT Compliant	
Hydraulic Components		Hydraulic Tilt Cylinder (MX) Manually Operated	
Warranty		Limited 3-Year Warranty	
DIMENSIONS			
Overall Length	276	300	324

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 23	7 x 25	7 x 27	7 x 29
Model #	H8218MXL-140	H8220MXL-140	H8222MXL-140	H8224MXL-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	2700	2910	2830	2110
Payload	11300	11090	11170	11890
CHASSIS				
Frame	6" Steel Channel			
Tongue	6" Steel Channel, Fully Wrapped			
Crossmembers	3" Steel Channel, 16" On-Center			
Coupler	2-5/16" Adjustable, Posi-Lock			
Tongue Jack	12K Drop Leg, Set-Back			
Bulkhead	HD Tube			
Dovetail	Reverse Taper Cut			
Fenders	Double Break Tread Plate			
Axle	(2) 7000 lb. Drop Slipper Spring Brake			
Hubs	Easy Lube			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Board Retainers			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Exterior Storage	Spare Tire Carrier			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	Hydraulic Tilt Cylinder (MX) Manually Operated			
Warranty	Limited 3-Year Warranty			
DIMENSIONS				
Overall Length	276	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 23	7 x 25	7 x 27	7 x 29
Model #	H8218MX-070	H8220MX-070	H8222MX-070	H8224MX-070
CAPACITIES				
GVWR (lbs)			7000	
GAWR (lbs/axle)			3500	
Curb Weight	1900	2010	2210	2450
Payload	5100	4990	4790	4550
CHASSIS				
Frame			5" Steel Channel	
Tongue			5" Steel Channel, Fully Wrapped	
Crossmembers			3" Steel Channel, 16" On-Center	
Coupler			2-5/16" A-Frame, Posi-Lock	
Deck Width			82.25	
Deck Height			23.25	
Tongue Jack			7K Drop Leg, Set-Back	
Dovetail			Reverse Taper Cut	
Fenders			Double Break Tread Plate	
Axle			(2) 3500 lb. Spring Brake	
Hubs			Easy Lube	
Tires			ST205/75R15C 6-PR	
Wheels			15", 5-Hole Steel	
Exterior Finish			Industrial Grade Polymer Finish	
Decking			2" Pressure Treated Pine, Board Retainers	
Tie Downs			Banjo Tie-Downs, Stake Pockets	
Exterior Storage			Spare Tire Carrier	
Wiring			Sealed Wiring Harness	
Exterior Lights			Full LED, DOT Compliant	
Hydraulic Components			Hydraulic Tilt Cylinder (MX) Manually Operated	
Warranty			Limited 3-Year Warranty	
Height Overall			33	
Width Interior			82.25	
Load Angle			12	
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width			82.25	
Deck Height			23.25	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 23	7 x 25	7 x 27	7 x 29
Model #	H8218MX-100	H8220MX-100	H8222MX-100	H8224MX-100
CAPACITIES				
GVWR (lbs)			9900	
GAWR (lbs/axle)			5200	
Curb Weight	2300	2450	2700	2830
Payload	7600	7450	7200	7070
CHASSIS				
Frame			6" Steel Channel	
Tongue			5" Steel Channel, Fully Wrapped	
Crossmembers			3" Steel Channel, 16" On-Center	
Coupler			2-5/16" A-Frame, Posi-Lock	
Deck Width				82.25
Deck Height				23.25
Tongue Jack			7K Drop Leg, Set-Back	
Dovetail			Reverse Taper Cut	
Fenders			Double Break Tread Plate	
Axle			(2) 5200 lb. Spring Brake	
Hubs			Easy Lube	
Tires			ST225/75R15D 8-PR	
Wheels			15", 6-Hole Steel	
Exterior Finish			Industrial Grade Polymer Finish	
Decking			2" Pressure Treated Pine, Board Retainers	
Tie Downs			Banjo Tie-Downs, Stake Pockets	
Exterior Storage			Spare Tire Carrier	
Wiring			Sealed Wiring Harness	
Exterior Lights			Full LED, DOT Compliant	
Hydraulic Components			Hydraulic Tilt Cylinder (MX) Manually Operated	
Warranty			Limited 3-Year Warranty	
Height Overall				33
Width Interior				82.25
Load Angle			11	9
DIMENSIONS				
Overall Length	276	300	324	348
Deck Width				82.25
Deck Height				23.25

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 23	7 x 25	7 x 27	7 x 29
Model #	H8218MX-140	H8220MX-140	H8222MX-140	H8224MX-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	2650	2800	3050	3150
Payload	11350	11200	10950	10850
CHASSIS				
Frame	6" Steel Channel			
Tongue	6" Steel Channel, Fully Wrapped			
Crossmembers	3" Steel Channel, 16" On-Center			
Coupler	2-5/16" Adjustable, Posi-Lock			
Tongue Jack	12K Drop Leg, Set-Back			
Dovetail	Reverse Taper Cut			
Fenders	Double Break Tread Plate			
Axle	(2) 7000 lb. Slipper Spring Brake			
Hubs	Easy Lube			
Tires	ST235/80R16E 10-PR			
Wheels	16", 8-Hole Steel			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine, Board Retainers			
Tie Downs	Banjo Tie-Downs, Stake Pockets			
Exterior Storage	Spare Tire Carrier			
Wiring	Sealed Wiring Harness			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	Hydraulic Tilt Cylinder (MX) Manually Operated			
Warranty	Limited 3-Year Warranty			
DIMENSIONS				
Overall Length	276	300	324	348

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.