



SPECIFICATIONS -CARGO STEEL ENCLOSED HHSERTCHR HH SERIES CAR HAULER ROUND TOP

	8.5 x 20	8.5 x 20	8.5 x 22	8.5 x 22	8.5 x 22	8.5 x 22
Model #	H10120RTCHV-100	H10120RTCHV-140	H10122RTCH-140	H10122RTCHV-100	H10122RTCH-100	H10122RTCHV-140
CAPACITIES						
GVWR (lbs)	9900	14000		9900		14000
GAWR (lbs/axle)	5200	7000		5200		7000
Curb Weight	3350	3600	3690	3420	3350	3620
Payload	6550	10400	10310	6480	6550	10380
CHASSIS						
Frame	6" Steel Channel					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable		2-5/16" A-Frame, Posi-Lock		2-5/16" Adjustable
Tongue Jack	2K Coupler Mounted	7K Drop Leg, Set-Back		2K Coupler Mounted		7K Drop Leg, Set-Back
Wall Studs	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center		Steel Tube, 24" On-Center		Steel Tube, 16" On-Center
Roof Bows	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center		Galvanized Steel Tube, 24" On-Center		Galvanized Steel Tube, 16" On-Center
Front Profile		Round		Round		
Dovetail	4' Interior					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR	ST235/80R16E 10-PR		ST225/75R15D 8-PR		ST235/80R16E 10-PR
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8.5 x 24	8.5 x 24	8.5 x 26	8.5 x 26	8.5 x 26	8.5 x 26
Model #	H10124RTCHV-140	H10124RTCHV-100	H10126RTCH-100	H10126RTCH-140	H10126RTCHV-140	H10126RTCHV-100
CAPACITIES						
GVWR (lbs)	14000	9900		14000		9900
GAWR (lbs/axle)	7000	5200		7000		5200
Curb Weight	3780	3560	3880	4025	4350	3750
Payload	10220	6340	6020	9975	9650	6150
CHASSIS						
Frame	6" Steel Channel					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock		2-5/16" Adjustable		2-5/16" A-Frame, Posi-Lock
Tongue Jack	7K Drop Leg, Set-Back	2K Coupler Mounted		7K Drop Leg, Set-Back		2K Coupler Mounted
Wall Studs	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center		Steel Tube, 16" On-Center		Steel Tube, 24" On-Center
Roof Bows	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center		Galvanized Steel Tube, 16" On-Center		Galvanized Steel Tube, 24" On-Center

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 24	8.5 x 24	8.5 x 26	8.5 x 26	8.5 x 26	8.5 x 26
Front Profile	Round					
Dovetail	4' Interior					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8.5 x 28	8.5 x 28	8.5 x 20	8.5 x 20	8.5 x 24	8.5 x 24
Model #	H10128RTCHV-140	H10128RTCHV-100	H10120RTCH-140	H10120RTCH-100	H10124RTCH-140	H10124RTCH-100
CAPACITIES						
GVWR (lbs)	14000	9900	14000	9900	14000	9900
GAWR (lbs/axle)	7000	5200	7000	5200	7000	5200
Curb Weight	4550	4110	3530	3250	4070	3490
Payload	9450	5790	10470	6650	9930	6410
CHASSIS						
Frame	6" Steel Channel					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock
Deck Width	98.5					
Deck Length	249			297		
Deck Height	23		22		22	
Tongue Jack	7K Drop Leg, Set-Back	2K Coupler Mounted	7K Drop Leg, Set-Back	2K Coupler Mounted	7K Drop Leg, Set-Back	2K Coupler Mounted
Wall Studs	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center
Roof Bows	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center
Front Profile	Round					
Dovetail	4' Interior					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Round Top					
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall			107	106	107	106

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 28	8.5 x 28	8.5 x 20	8.5 x 20	8.5 x 24	8.5 x 24
Height Interior					82	
Height Rear Opening					74.5	
Width Interior					98.5	
Width Between Fender					82	
Width Rear Opening					95	
DIMENSIONS						
Overall Length				293		341
Deck Length				249		297
Deck Width					98.5	
Deck Height			23	22	23	22
		8.5 x 28			8.5 x 28	
Model #		H10128RTCH-140			H10128RTCH-100	
CAPACITIES						
GVWR (lbs)		14000			9900	
GAWR (lbs/axle)		7000			5200	
Curb Weight					4030	
Payload					5870	
CHASSIS						
Frame				6" Steel Channel		
Tongue				6" x 2" Steel Triple Tube		
Crossmembers				Steel Formed Channel, 16" On-Center		
Coupler		2-5/16" Adjustable			2-5/16" A-Frame, Posi-Lock	
Deck Width				98.5		
Deck Length				345		
Deck Height		23			22	
Tongue Jack		7K Drop Leg, Set-Back			2K Coupler Mounted	
Wall Studs		Steel Tube, 16" On-Center			Steel Tube, 24" On-Center	
Roof Bows		Galvanized Steel Tube, 16" On-Center			Galvanized Steel Tube, 24" On-Center	
Front Profile				Round		
Dovetail				4' Interior		
Ramp(s)				4000 lb. with Assist		
Side Door				36" Wide Flush Lock, Cast Aluminum Holdback		
Hubs				Easy Lube		
Tires		ST235/80R16E 10-PR			ST225/75R15D 8-PR	
Exterior Finish				.030" Aluminum		
Protective Coating(s)				Polyethylene Vapor Barrier		
Stone Guard				24" ATP		
Roof				Round Top		
Tie Downs				(4) Floor Mounted, Non-swivel Recessed D-Rings		
Interior Walls				Engineered Wood		
Flooring				3/4" Engineered Wood		
Wiring				Enclosed in Conduit		
Exterior Lights				Full LED, DOT Compliant		
Warranty				Limited 3-Year Warranty		
Height Overall		107			106	
Height Interior				82		
Height Rear Opening				74.5		
Width Interior				98.5		
Width Between Fender				82		
Width Rear Opening				95		
DIMENSIONS						

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

8.5 x 28

8.5 x 28

Overall Length	389	
Deck Length	345	
Deck Width	98.5	
Deck Height	23	22

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.