

**SPECIFICATIONS -CARGO STEEL ENCLOSED**  
**HHSECHCR10,HHSETCHCR14,HHSETCHCR16,HHSETGNFT10,HHSETGNFT14,HHSETGNFT16**  
**TOPLINE CAR HAULER RT 10K**

	8.5 x 26	8.5 x 30	8.5 x 20	8.5 x 24	8.5 x 28
<b>Model #</b>	H10126CRCH-100	H10130CRCH-100	H10120CRCH-100	H10124CRCH-100	H10128CRCH-100
<b>CAPACITIES</b>					
<b>GVWR (lbs)</b>	9900				
<b>GAWR (lbs/axle)</b>	5200				
<b>Curb Weight</b>	4480	4690	3750	4060	
<b>Payload</b>	5420	5210	6150	5840	
<b>CHASSIS</b>					
<b>Frame</b>	6" Steel Channel				
<b>Tongue</b>	6" x 2" Steel Triple Tube				
<b>Crossmembers</b>	Steel Tube, 16" On-Center				
<b>Coupler</b>	2-5/16" A-Frame, Posi-Lock				
<b>Deck Width</b>				98.5	
<b>Deck Length</b>			249	297	345
<b>Deck Height</b>				24	
<b>Tongue Jack</b>	7K Drop Leg, Set-Back				
<b>Wall Studs</b>	Steel Tube, 16" On-Center				
<b>Roof Bows</b>	Galvanized Steel Tube, 16" On-Center				
<b>Dovetail</b>	4' Interior				
<b>Ramp(s)</b>	4000 lb. with Assist and Integrated Transition				
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback				
<b>Hubs</b>	Easy Lube				
<b>Tires</b>	ST225/75R15D 8-PR				
<b>Exterior Finish</b>	.040" Aluminum				
<b>Protective Coating(s)</b>	Polyethylene Vapor Barrier				
<b>Stone Guard</b>	24" ATP				
<b>Roof</b>	Round Top				
<b>Interior Walls</b>	Engineered Wood				
<b>Flooring</b>	3/4" Engineered Wood				
<b>Wiring</b>	Enclosed in Conduit				
<b>Exterior Lights</b>	Full LED, DOT Compliant				
<b>Warranty</b>	Limited 3-Year Warranty				
<b>Height Overall</b>				106	
<b>Height Interior</b>				83	
<b>Height Rear Opening</b>				76.5	
<b>Width Interior</b>				98.5	
<b>Width Between Fender</b>				82	
<b>Width Rear Opening</b>				95	
<b>DIMENSIONS</b>					
<b>Overall Length</b>			295	343	391
<b>Deck Length</b>			249	297	345
<b>Deck Width</b>				98.5	
<b>Deck Height</b>				24	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

**SPECIFICATIONS -CARGO STEEL ENCLOSED**  
**HHSECHCR10,HHSETCHCR14,HHSETCHCR16,HHSETGNFT10,HHSETGNFT14,HHSETGNFT16**  
**TOPLINE GOOSENECK CH 10K**

	8.5 x 20	8.5 x 24	8.5 x 26	8.5 x 26	8.5 x 28	8.5 x 24
<b>Model #</b>	H10120CRCHGNV-100	H10124CRCHGNV-100	H10126CRCHGNV-100	H10126CRCHGN-100	H10128CRCHGNV-100	H10124CRCHGN-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5200					
<b>Curb Weight</b>	5000	5330			5980	
<b>Payload</b>	4900	4570			3920	
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	Full Tubular Steel Gooseneck					
<b>Crossmembers</b>	Steel Tube, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable Gooseneck					
<b>Coupler Height</b>						35-43
<b>Deck Width</b>						98.5
<b>Deck Length</b>						282
<b>Deck Height</b>						26
<b>Tongue Jack</b>	Dual 12K Drop Leg					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Galvanized Steel Tube, 16" On-Center					
<b>Front Profile</b>	V-Nose		Round		V-Nose	Round
<b>Dovetail</b>	4' Interior					
<b>Ramp(s)</b>	4000 lb. with Assist and Integrated Transition					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Teardrop Smooth Aluminum					
<b>Axle</b>	(2) 5200 lb. Torsion Brake					
<b>Hubs</b>	Easy Lube					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Protective Coating(s)</b>	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
<b>Exterior Trim</b>	Polished Cast Aluminum Roof Corners					
<b>Stone Guard</b>	Lower ATP Bulkhead					
<b>Roof</b>	.030 Aluminum Sheet, Round Top					
<b>Roof Cap</b>	Custom Formed Fiberglass					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED Dome Lights, Wall Mount					
<b>Wiring</b>	Enclosed in Conduit					
<b>Exterior Lights</b>	Full LED, DOT Compliant					
<b>Warranty</b>	Limited 3-Year Warranty					
<b>Height Overall</b>						108
<b>Height Interior</b>						83
<b>Height Rear Opening</b>						74.5
<b>Width Interior</b>						98.5
<b>Width Between Fender</b>						82.5
<b>Width Rear Opening</b>						95
<b>DIMENSIONS</b>						
<b>Overall Length</b>						388
<b>Deck Length</b>						282

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 20	8.5 x 24	8.5 x 26	8.5 x 26	8.5 x 28	8.5 x 24
<b>Deck Width</b>						98.5
<b>Deck Height</b>						26
<b>Coupler Height</b>						35-43

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

**SPECIFICATIONS -CARGO STEEL ENCLOSED**  
**HHSECHCR10,HHSETCHCR14,HHSETCHCR16,HHSETGNFT10,HHSETGNFT14,HHSETGNFT16**  
**TOPLINE CAR HAULER RT 14K**

	8.5 x 20		8.5 x 22		8.5 x 24		8.5 x 26		8.5 x 28	
<b>Model #</b>	H10120CRCHV-140		H10122CRCHV-140		H10122CRCH-140		H10124CRCHV-140		H10126CRCH-140	
<b>CAPACITIES</b>										
<b>GVWR (lbs)</b>	14000									
<b>GAWR (lbs/axle)</b>	7000									
<b>Curb Weight</b>	4200		4150			4330		5070		4450
<b>Payload</b>	9800		9850			9670		8930		9550
<b>CHASSIS</b>										
<b>Frame</b>	6" x 2" Steel Tube									
<b>Tongue</b>	6" x 2" Steel Triple Tube									
<b>Crossmembers</b>	Steel Tube, 16" On-Center									
<b>Coupler</b>	2-5/16" Adjustable									
<b>Tongue Jack</b>	7K Drop Leg, Set-Back									
<b>Wall Studs</b>	Steel Tube, 16" On-Center									
<b>Roof Bows</b>	Galvanized Steel Tube, 16" On-Center									
<b>Front Profile</b>	V-Nose		Round		V-Nose		Round		V-Nose	
<b>Dovetail</b>	4' Interior									
<b>Ramp(s)</b>	4000 lb. with Assist and Integrated Transition									
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback									
<b>Fenders</b>	Teardrop Smooth Aluminum									
<b>Axle</b>	(2) 7000 lb. Torsion Brake									
<b>Hubs</b>	Easy Lube									
<b>Tires</b>	ST235/80R16E 10-PR									
<b>Wheels</b>	16", 8-Hole Aluminum									
<b>Exterior Finish</b>	.040" Aluminum									
<b>Protective Coating(s)</b>	Textured Polyurea all Exposed Steel									
<b>Exterior Trim</b>	Polished Cast Aluminum Roof Corners									
<b>Stone Guard</b>	24" ATP									
<b>Roof</b>	.030 Aluminum Sheet, Round Top									
<b>Roof Cap</b>	Custom Formed Fiberglass									
<b>Interior Walls</b>	Engineered Wood									
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions									
<b>Flooring</b>	3/4" Engineered Wood									
<b>Interior Lights</b>	(2) LED Dome Lights, Wall Mount									
<b>Wiring</b>	Enclosed in Conduit									
<b>Exterior Lights</b>	Full LED, DOT Compliant									
<b>Warranty</b>	Limited 3-Year Warranty									
	8.5 x 28		8.5 x 30		8.5 x 30		8.5 x 20		8.5 x 24	
<b>Model #</b>	H10128CRCHV-140		H10130CRCH-140		H10130CRCHV-140		H10120CRCH-140		H10124CRCH-140	
<b>CAPACITIES</b>										
<b>GVWR (lbs)</b>	14000									
<b>GAWR (lbs/axle)</b>	7000									
<b>Curb Weight</b>			5000			4000		4275		
<b>Payload</b>			9000			10000		9725		
<b>CHASSIS</b>										
<b>Frame</b>	6" x 2" Steel Tube									
<b>Tongue</b>	6" x 2" Steel Triple Tube									
<b>Crossmembers</b>	Steel Tube, 16" On-Center									
<b>Coupler</b>	2-5/16" Adjustable									
<b>Deck Width</b>						99.5		100.5		101.5
<b>Deck Length</b>						249		297		345

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 28	8.5 x 30	8.5 x 30	8.5 x 20	8.5 x 24	8.5 x 28
Deck Height					25	
Tongue Jack				7K Drop Leg, Set-Back		
Wall Studs				Steel Tube, 16" On-Center		
Roof Bows				Galvanized Steel Tube, 16" On-Center		
Front Profile	V-Nose	Round		V-Nose		Round
Dovetail				4' Interior		
Ramp(s)				4000 lb. with Assist and Integrated Transition		
Side Door				36" Wide Flush Lock, Cast Aluminum Holdback		
Fenders				Teardrop Smooth Aluminum		
Axle				(2) 7000 lb. Torsion Brake		
Hubs				Easy Lube		
Tires				ST235/80R16E 10-PR		
Wheels				16", 8-Hole Aluminum		
Exterior Finish				.040" Aluminum		
Protective Coating(s)				Textured Polyurea all Exposed Steel		
Exterior Trim				Polished Cast Aluminum Roof Corners		
Stone Guard				24" ATP		
Roof				.030 Aluminum Sheet, Round Top		
Roof Cap				Custom Formed Fiberglass		
Interior Walls				Engineered Wood		
Interior Trim				Extruded Aluminum Wall Transitions		
Flooring				3/4" Engineered Wood		
Interior Lights				(2) LED Dome Lights, Wall Mount		
Wiring				Enclosed in Conduit		
Exterior Lights				Full LED, DOT Compliant		
Warranty				Limited 3-Year Warranty		
Height Overall					107	
Height Interior					83	
Height Rear Opening					76.5	
Width Interior				99.5	100.5	101.5
Width Between Fender					82	
Width Rear Opening					95	
<b>DIMENSIONS</b>						
Overall Length				331	343	391
Deck Length				249	297	345
Deck Width				99.5	100.5	101.5
Deck Height					25	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

**SPECIFICATIONS -CARGO STEEL ENCLOSED**  
**HHSECHCR10,HHSETCHCR14,HHSETCHCR16,HHSETGNFT10,HHSETGNFT14,HHSETGNFT16**  
**TOPLINE GOOSENECK CH 14K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 26	8.5 x 28
<b>Model #</b>	H10120CRCHGNV-140	H10122CRCHGNV-140	H10124CRCHGNV-140	H10126CRCHGN-140	H10126CRCHGNV-140	H10128CRCHGNV-140
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	14000					
<b>GAWR (lbs/axle)</b>	7000					
<b>Curb Weight</b>	5400	5250	5550		5965	
<b>Payload</b>	8600	8750	8450		8035	
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	Full Tubular Steel Gooseneck					
<b>Crossmembers</b>	Steel Tube, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable Gooseneck					
<b>Tongue Jack</b>	Dual 12K Drop Leg					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Galvanized Steel Tube, 16" On-Center					
<b>Front Profile</b>	V-Nose			Round		V-Nose
<b>Dovetail</b>	4' Interior					
<b>Ramp(s)</b>	4000 lb. with Assist and Integrated Transition					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Teardrop Smooth Aluminum					
<b>Axle</b>	(2) 7000 lb. Torsion Brake					
<b>Hubs</b>	Easy Lube					
<b>Tires</b>	ST235/80R16E 10-PR					
<b>Wheels</b>	16", 8-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Protective Coating(s)</b>	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
<b>Exterior Trim</b>	Polished Cast Aluminum Roof Corners					
<b>Stone Guard</b>	Lower ATP Bulkhead					
<b>Roof</b>	.030 Aluminum Sheet, Round Top					
<b>Roof Cap</b>	Custom Formed Fiberglass					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED Dome Lights, Wall Mount					
<b>Wiring</b>	Enclosed in Conduit					
<b>Exterior Lights</b>	Full LED, DOT Compliant					
<b>Warranty</b>	Limited 3-Year Warranty					
	8.5 x 30	8.5 x 30	8.5 x 32	8.5 x 20	8.5 x 24	8.5 x 28
<b>Model #</b>	H10130CRCHGN-140	H10130CRCHGNV-140	H10132CRCHGNV-140	H10120CRCHGN-140	H10124CRCHGN-140	H10128CRCHGN-140
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	14000					
<b>GAWR (lbs/axle)</b>	7000					
<b>Curb Weight</b>		5950			5500	5870
<b>Payload</b>		8050			8500	8130
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	Full Tubular Steel Gooseneck					
<b>Crossmembers</b>	Steel Tube, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable Gooseneck					
<b>Coupler Height</b>					35-43	
<b>Deck Width</b>				99.5	100.5	101.5

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 30	8.5 x 30	8.5 x 32	8.5 x 20	8.5 x 24	8.5 x 28
Deck Length				234	282	330
Deck Height					26	
Tongue Jack	Dual 12K Drop Leg					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	Round	V-Nose			Round	
Dovetail	4' Interior					
Ramp(s)	4000 lb. with Assist and Integrated Transition					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 7000 lb. Torsion Brake					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.040" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Exterior Trim	Polished Cast Aluminum Roof Corners					
Stone Guard	Lower ATP Bulkhead					
Roof	.030 Aluminum Sheet, Round Top					
Roof Cap	Custom Formed Fiberglass					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall				107	109	
Height Interior					83	
Height Rear Opening					74.5	
Width Interior				99.5	100.5	101.5
Width Between Fender					82.5	
Width Rear Opening					95	
<b>DIMENSIONS</b>						
Overall Length				340	388	436
Deck Length				234	282	330
Deck Width				99.5	100.5	101.5
Deck Height					26	
Coupler Height					35-43	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

**SPECIFICATIONS -CARGO STEEL ENCLOSED**  
**HHSECHCR10,HHSETCHCR14,HHSETCHCR16,HHSETGNFT10,HHSETGNFT14,HHSETGNFT16**  
**TOPLINE CAR HAULER RT 16K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 24	8.5 x 26	8.5 x 28
<b>Model #</b>	H10120CRCHV-160	H10122CRCHV-160	H10124CRCHV-160	H10124CRCH-160	H10126CRCHV-160	H10128CRCHV-160
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	16000					
<b>GAWR (lbs/axle)</b>	8000					
<b>Curb Weight</b>	4800					
<b>Payload</b>	11200					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Steel Tube, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable					
<b>Tongue Jack</b>	7K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Galvanized Steel Tube, 16" On-Center					
<b>Front Profile</b>	V-Nose		Round		V-Nose	
<b>Dovetail</b>	4' Interior					
<b>Ramp(s)</b>	4000 lb. with Assist and Integrated Transition					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Teardrop Smooth Aluminum					
<b>Axle</b>	(2) 8000 lb. Torsion Brake					
<b>Hubs</b>	Oil Bath					
<b>Wheels</b>	17.5", 8-Hole Steel					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Protective Coating(s)</b>	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
<b>Exterior Trim</b>	Polished Cast Aluminum Roof Corners					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	.030 Aluminum Sheet, Round Top					
<b>Roof Cap</b>	Custom Formed Fiberglass					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED Dome Lights, Wall Mount					
<b>Wiring</b>	Enclosed in Conduit					
<b>Exterior Lights</b>	Full LED, DOT Compliant					
<b>Warranty</b>	Limited 3-Year Warranty					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

**SPECIFICATIONS -CARGO STEEL ENCLOSED**  
**HHSECHCR10,HHSETCHCR14,HHSETCHCR16,HHSETGNFT10,HHSETGNFT14,HHSETGNFT16**  
**TOPLINE GOOSENECK CH 16K**

	8.5 x 20	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 30
<b>Model #</b>	H10120CRCHGNV-160	H10124CRCHGNV-160	H10126CRCHGNV-160	H10128CRCHGNV-160	H10130CRCHGN-160	H10122CRCHGNV-160
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>				16000		
<b>GAWR (lbs/axle)</b>				8000		
<b>Curb Weight</b>	7150					
<b>Payload</b>	8850					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	Full Tubular Steel Gooseneck					
<b>Crossmembers</b>	Steel Tube, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable Gooseneck					
<b>Tongue Jack</b>	Dual 12K Drop Leg					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Galvanized Steel Tube, 16" On-Center					
<b>Front Profile</b>	V-Nose				Round	V-Nose
<b>Dovetail</b>	4' Interior					
<b>Ramp(s)</b>	4000 lb. with Assist and Integrated Transition					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Teardrop Smooth Aluminum					
<b>Axle</b>	(2) 8000 lb. Torsion Brake					
<b>Hubs</b>	Oil Bath					
<b>Wheels</b>	17.5", 8-Hole Steel					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Protective Coating(s)</b>	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
<b>Exterior Trim</b>	Polished Cast Aluminum Roof Corners					
<b>Stone Guard</b>	Lower ATP Bulkhead					
<b>Roof</b>	.030 Aluminum Sheet, Round Top					
<b>Roof Cap</b>	Custom Formed Fiberglass					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED Dome Lights, Wall Mount					
<b>Wiring</b>	Enclosed in Conduit					
<b>Exterior Lights</b>	Full LED, DOT Compliant					
<b>Warranty</b>	Limited 3-Year Warranty					
	8.5 x 30	8.5 x 32	8.5 x 24	8.5 x 24	8.5 x 28	8.5 x 28
<b>Model #</b>	H10130CRCHGNV-160	H10132CRCHGNV-160	H10124CRCHGN-160	H10124CRCHGN-160	H10128CRCHGN-160	H10128CRCHGN-160
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>				16000		
<b>GAWR (lbs/axle)</b>				8000		
<b>Curb Weight</b>	6430					
<b>Payload</b>	9570					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	Full Tubular Steel Gooseneck					
<b>Crossmembers</b>	Steel Tube, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable Gooseneck					
<b>Coupler Height</b>					35-43	
<b>Deck Width</b>				104.5		105.5
<b>Deck Length</b>				282		330

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 30	8.5 x 32	8.5 x 24	8.5 x 28
Deck Height				26
Tongue Jack			Dual 12K Drop Leg	
Wall Studs			Steel Tube, 16" On-Center	
Roof Bows			Galvanized Steel Tube, 16" On-Center	
Front Profile		V-Nose		Round
Dovetail			4' Interior	
Ramp(s)			4000 lb. with Assist and Integrated Transition	
Side Door			36" Wide Flush Lock, Cast Aluminum Holdback	
Fenders			Teardrop Smooth Aluminum	
Axle			(2) 8000 lb. Torsion Brake	
Hubs			Oil Bath	
Wheels			17.5", 8-Hole Steel	
Exterior Finish			.040" Aluminum	
Protective Coating(s)			Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel	
Exterior Trim			Polished Cast Aluminum Roof Corners	
Stone Guard			Lower ATP Bulkhead	
Roof			.030 Aluminum Sheet, Round Top	
Roof Cap			Custom Formed Fiberglass	
Interior Walls			Engineered Wood	
Interior Trim			Extruded Aluminum Wall Transitions	
Flooring			3/4" Engineered Wood	
Interior Lights			(2) LED Dome Lights, Wall Mount	
Wiring			Enclosed in Conduit	
Exterior Lights			Full LED, DOT Compliant	
Warranty			Limited 3-Year Warranty	
Height Overall				109
Height Interior				83
Height Rear Opening				74.5
Width Interior			104.5	105.5
Width Between Fender				82.5
Width Rear Opening				95
<b>DIMENSIONS</b>				
Overall Length			388	436
Deck Length			282	330
Deck Width			104.5	105.5
Deck Height				26
Coupler Height				35-43

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.