



SPECIFICATIONS -CARGO STEEL ENCLOSED HHSEFTV,HHSETFTV10,HHSETFTV14,HHSETFTV7 HH SERIES CARGO FLAT TOP 10K

	8 x 14	8.5 x 14	8.5 x 16	8 x 16	8.5 x 18	8 x 18
Model #	H9614TFTV-100	H10114TFTV-100	H10116TFTV-100	H9616TFTV-100	H10118TFTV-100	H9618TFTV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight			3000	2725	3370	2900
Payload			6900	7175	6530	7000
CHASSIS						
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Tongue	4" x 2" Steel Tube	4" x 2" Steel Triple Tube		4" x 2" Steel Tube	6" x 2" Steel Triple Tube	6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	V-Nose					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Steel					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8 x 20	8.5 x 20	8 x 22	6 x 12	7 x 12	7 x 14
Model #	H9620TFTV-100	H10120TFTV-100	H9622TFTV-100	H7212TFTV-100	H8412TFTV-100	H8414TFTV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	3200	3290	3600		2200	2550
Payload	6700	6610	6300		7700	7350
CHASSIS						
Frame	6" x 2" Steel Tube			4" x 2" Steel Tube		
Tongue	6" x 2" Steel Tube	6" x 2" Steel Triple Tube	6" x 2" Steel Tube	4" x 2" Steel Tube		
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width				69		82
Deck Length					171	195
Deck Height					20	
Tongue Jack	2K Coupler Mounted					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8 x 20	8.5 x 20	8 x 22	6 x 12	7 x 12	7 x 14
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	V-Nose					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Steel					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall				94		98
Height Interior					73	
Height Rear Opening					69	
Width Interior				69		82
Width Rear Opening				66		78
DIMENSIONS						
Overall Length				210	214	238
Deck Length					171	195
Deck Width				69		82
Deck Height					20	
	7 x 16		7 x 18		7 x 20	
Model #	H8416TFTV-100		H8418TFTV-100		H8420TFTV-100	
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	2290		2630			2870
Payload	7610		7270			7030
CHASSIS						
Frame	4" x 2" Steel Tube		6" x 2" Steel Tube			
Tongue	4" x 2" Steel Tube		6" x 2" Steel Tube			
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	82					
Deck Length	219		243			267
Deck Height	20			21		
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	V-Nose					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 16	7 x 18	7 x 20
Tires	ST225/75R15D 8-PR		
Wheels	15", 6-Hole Steel		
Exterior Finish	.030" Aluminum		
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel		
Stone Guard	24" ATP		
Roof	Flat Top .024 Aluminum Sheeted		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED Dome Lights, Wall Mount		
Wiring	Enclosed in Conduit		
Exterior Lights	Full LED, DOT Compliant		
Warranty	Limited 3-Year Warranty		
Height Overall	98		100
Height Interior		73	
Height Rear Opening		69	
Width Interior		82	
Width Rear Opening		78	
DIMENSIONS			
Overall Length	262	286	322
Deck Length	219	243	267
Deck Width		82	
Deck Height	20		21

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED HHSEFTV,HHSETFTV10,HHSETFTV14,HHSETFTV7 HH SERIES CARGO FLAT TOP 14K

	7 x 10	7 x 12	8 x 12	6 x 12	8 x 14	7 x 14
Model #	H8410TFTV-140	H8412TFTV-140	H9612TFTV-140	H7212TFTV-140	H9614TFTV-140	H8414TFTV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight						2690
Payload						11310
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	V-Nose					
Ramp(s)			4000 lb. with Assist		4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Steel					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	8.5 x 14	8.5 x 16	8 x 16	7 x 16	8 x 18	8.5 x 18
Model #	H10114TFTV-140	H10116TFTV-140	H9616TFTV-140	H8416TFTV-140	H9618TFTV-140	H10118TFTV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight		3450		2930	3250	3650
Payload		10550		11070	10750	10350
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	V-Nose					
Ramp(s)		4000 lb. with Assist			4000 lb. with Assist	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 14	8.5 x 16	8 x 16	7 x 16	8 x 18	8.5 x 18
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Steel					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	7 x 18	8.5 x 20	7 x 20	8 x 20		
Model #	H8418TFTV-140	H10120TFTV-140	H8420TFTV-140	H9620TFTV-140		
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight		3490				3570
Payload		10510				10430
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Front Profile	V-Nose					
Ramp(s)		4000 lb. with Assist				4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Steel					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED HHSEFTV,HHSETFTV10,HHSETFTV14,HHSETFTV7 HH SERIES CARGO FLAT TOP 03-05K

	5 x 8	5 x 10	7 x 10	6 x 10	6 x 12	7 x 12
Model #	H608SFTV-050	H6010SFTV-050	H8410SFTV-050	H7210SFTV-050	H7212SFTV-050	H8412SFTV-050
CAPACITIES						
GVWR (lbs)	5000					
GAWR (lbs/axle)	5000			5200		
Curb Weight	1330		1705	1485	1550	1825
Payload	3670		3295	3515	3450	3175
CHASSIS						
Frame	4" x 2" Steel Tube					
Tongue	4" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue Jack	2K Swivel Jack with Foot					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Square Rolled Smooth Aluminum					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Interior Lights	(1) LED					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
	6 x 14	5 x 8	5 x 10	6 x 10	7 x 10	6 x 12
Model #	H7214SFTV-050	H608SFTV-035	H6010SFTV-035	H7210SFTV-035	H8410SFTV-035	H7212SFTV-035
CAPACITIES						
GVWR (lbs)	5000		2990			
GAWR (lbs/axle)	5200		3500			
Curb Weight	1675	1030	1230	1320	1530	1375
Payload	3325	1960	1760	1670	1460	1615
CHASSIS						
Frame	4" x 2" Steel Tube		3" x 2" Steel Tube		4" x 2" Steel Tube	3" x 2" Steel Tube
Tongue	4" x 2" Steel Tube		3" x 2" Steel Tube		4" x 2" Steel Tube	3" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center		Steel Formed Channel, 24" On-Center			
Coupler	2-5/16" A-Frame, Posi-Lock		2" A-Frame, Posi-Lock			
Deck Width			57	69	81	69
Deck Length			123	147		171
Deck Height	18					
Tongue Jack	2K Swivel Jack with Foot					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback			32" Wide Flush Lock, Cast Aluminum Holdback		
Fenders	Square Rolled Smooth Aluminum					
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR			ST205/75R15C 6-PR		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	6 x 14	5 x 8	5 x 10	6 x 10	7 x 10	6 x 12
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Interior Lights	(1) LED					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall		86		92	96	92
Height Interior		66			73	
Height Rear Opening		65			70	
Width Interior		57		69	81	69
Width Rear Opening		58		66	78	66
DIMENSIONS						
Overall Length		162		186		210
Deck Length		123		147		171
Deck Width		57		69	81	69
Deck Height				18		
	7 x 12	6 x 14				
Model #	H8412SFTV-035	H7214SFTV-035				
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
Curb Weight	1650	1500				
Payload	1340	1490				
CHASSIS						
Frame	4" x 2" Steel Tube	3" x 2" Steel Tube				
Tongue	4" x 2" Steel Tube	3" x 2" Steel Tube				
Crossmembers	Steel Formed Channel, 24" On-Center					
Coupler	2" A-Frame, Posi-Lock					
Deck Width	81	69				
Deck Length	171	195				
Deck Height	18					
Tongue Jack	2K Swivel Jack with Foot					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Square Rolled Smooth Aluminum					
Hubs	Easy Lube					
Tires	ST205/75R15C 6-PR					
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Interior Walls	Engineered Wood					
Flooring	3/4" Engineered Wood					
Interior Lights	(1) LED					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Height Overall	96	92				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	7 x 12	6 x 14
Height Interior		73
Height Rear Opening		70
Width Interior	81	69
Width Rear Opening	78	66
DIMENSIONS		
Overall Length	210	234
Deck Length	171	195
Deck Width	81	69
Deck Height		18

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -CARGO STEEL ENCLOSED HHSEFTV,HHSETFTV10,HHSETFTV14,HHSETFTV7 HH SERIES CARGO FLAT TOP 07K

	8.5 x 14		8 x 14		6 x 14		8 x 16		8.5 x 16		8 x 18	
Model #	H10114TFTV-070		H9614TFTV-070		H7214TFTV-070		H9616TFTV-070		H10116TFTV-070		H9618TFTV-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
Curb Weight	2500	2680	2050	2500	2600	2590						
Payload	4500	4320	4950	4500	4400	4410						
CHASSIS												
Frame	4" x 2" Steel Tube				4" x 2" Steel Tube				6" x 2" Steel Tube			
Tongue	4" x 2" Steel Triple Tube		4" x 2" Steel Tube				4" x 2" Steel Triple Tube		6" x 2" Steel Tube			
Crossmembers	Steel Formed Channel, 16" On-Center				Steel Formed Channel, 24" On-Center		Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock											
Tongue Jack	2K Coupler Mounted								2K Coupler Mounted			
Wall Studs	Steel Tube, 24" On-Center											
Roof Bows	Galvanized Steel Tube, 24" On-Center											
Front Profile	V-Nose											
Ramp(s)	4000 lb. with Assist								4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback				36" Wide Flush Lock		36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum											
Axle	(2) 3500 lb. Drop Spring Brake											
Hubs	Easy Lube								Easy Lube			
Tires	ST205/75R15C 6-PR											
Wheels	15", 5-Hole Steel								15", 5-Hole Steel			
Exterior Finish	.030" Aluminum											
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel								Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel			
Stone Guard	24" ATP											
Roof	Flat Top .024 Aluminum Sheeted											
Interior Walls	Engineered Wood								Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions								Extruded Aluminum Wall Transitions			
Interior Lights	(2) LED Dome Lights, Wall Mount											
Wiring	Sealed Wiring Harness											
Exterior Lights	Full LED, DOT Compliant											
Warranty	Limited 3-Year Warranty								Limited 3-Year Warranty			
	8.5 x 18		8 x 20		8.5 x 20		6 x 12		7 x 14		7 x 16	
Model #	H10118TFTV-070		H9620TFTV-070		H10120TFTV-070		H7212TFTV-070		H8414TFTV-070		H8416TFTV-070	
CAPACITIES												
GVWR (lbs)	7000											
GAWR (lbs/axle)	3500											
Curb Weight	2810	2760	3100	1750	2100	2220						
Payload	4190	4240	3900	5250	4900	4780						
CHASSIS												
Frame	6" x 2" Steel Tube								4" x 2" Steel Tube			
Tongue	6" x 2" Steel Triple Tube		6" x 2" Steel Tube		6" x 2" Steel Triple Tube		4" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center											
Coupler	2-5/16" A-Frame, Posi-Lock											
Deck Width									69		82	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 18	8 x 20	8.5 x 20	6 x 12	7 x 14	7 x 16
Deck Length				171	195	219
Deck Height					19	
Tongue Jack		2K Coupler Mounted				
Wall Studs		Steel Tube, 24" On-Center				
Roof Bows		Galvanized Steel Tube, 24" On-Center				
Front Profile		V-Nose				
Ramp(s)		4000 lb. with Assist				
Side Door		36" Wide Flush Lock, Cast Aluminum Holdback				
Fenders		Teardrop Smooth Aluminum				
Axle		(2) 3500 lb. Drop Spring Brake				
Hubs		Easy Lube				
Tires		ST205/75R15C 6-PR				
Wheels		15", 5-Hole Steel				
Exterior Finish		.030" Aluminum				
Protective Coating(s)		Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel				
Stone Guard		24" ATP				
Roof		Flat Top .024 Aluminum Sheeted				
Interior Walls		Engineered Wood				
Interior Trim		Extruded Aluminum Wall Transitions				
Interior Lights		(2) LED Dome Lights, Wall Mount				
Wiring		Sealed Wiring Harness				
Exterior Lights		Full LED, DOT Compliant				
Warranty		Limited 3-Year Warranty				
Height Overall				93		97
Height Interior					73	
Height Rear Opening					69	
Width Interior				69		82
Width Rear Opening				66		78
DIMENSIONS						
Overall Length				210	238	262
Deck Length				171	195	219
Deck Width				69		82
Deck Height					19	
			7 x 18	7 x 20		
Model #	H8418TFTV-070			H8420TFTV-070		
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2380				2470	
Payload	4620				4530	
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock					
Deck Width	82					
Deck Length	243				267	
Deck Height	20					
Wall Studs	Steel Tube, 24" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Front Profile	V-Nose					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

7 x 18

7 x 20

Axle	(2) 3500 lb. Drop Spring Brake	
Hubs	Easy Lube	
Tires	ST205/75R15C 6-PR	
Wheels	15", 5-Hole Steel	
Exterior Finish	.030" Aluminum	
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel	
Stone Guard	24" ATP	
Roof	Flat Top .024 Aluminum Sheeted	
Interior Walls	Engineered Wood	
Interior Trim	Extruded Aluminum Wall Transitions	
Interior Lights	(2) LED Dome Lights, Wall Mount	
Wiring	Sealed Wiring Harness	
Exterior Lights	Full LED, DOT Compliant	
Warranty	Limited 3-Year Warranty	
Height Overall	99	
Height Interior	73	
Height Rear Opening	69	
Width Interior	82	
Width Rear Opening	78	
DIMENSIONS		
Overall Length	286	322
Deck Length	243	267
Deck Width	82	
Deck Height	20	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.