



SPECIFICATIONS -CARGO STEEL ENCLOSED HH SERIES CAR HAULER FLAT TOP

	8.5 x 22	8.5 x 22	8.5 x 26	8.5 x 26	8.5 x 20	8.5 x 20
Model #	H10122FTCHV-100	H10122FTCHV-140	H10126FTCHV-100	H10126FTCHV-140	H10120FTCHV-100	H10120FTCHV-140
CAPACITIES						
GVWR (lbs)	9900	14000	9900	14000	9900	14000
GAWR (lbs/axle)	5200	7000	5200	7000	5200	7000
Curb Weight	3470	3930	3800		3600	3650
Payload	6430	10070	6100		6300	10350
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable
Deck Width						98.5
Deck Length						267
Deck Height					22	23
Tongue Jack	2K Coupler Mounted	7K Drop Leg, Set-Back	2K Coupler Mounted	7K Drop Leg, Set-Back	2K Coupler Mounted	7K Drop Leg, Set-Back
Wall Studs	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center
Roof Bows	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center
Front Profile	V-Nose					
Dovetail	4' Interior					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 5200 lb. Drop Spring Brake	(2) 7000 lb. Drop Spring Brake	(2) 5200 lb. Drop Spring Brake	(2) 7000 lb. Drop Spring Brake	(2) 5200 lb. Drop Spring Brake	(2) 7000 lb. Drop Spring Brake
Hubs	Easy Lube					
Tires	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR
Wheels	15", 6-Hole Steel	16", 8-Hole Steel	15", 6-Hole Steel	16", 8-Hole Steel	15", 6-Hole Steel	16", 8-Hole Steel
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Exterior Fastening	VHB Bonded (Screwless)					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Length Interior Box						267
Height Overall					98	99
Height Interior						73.5
Height Rear Opening						68
Width Interior						98.5

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 22	8.5 x 22	8.5 x 26	8.5 x 26	8.5 x 20	8.5 x 20
Width Between Fender						82
Width Rear Opening						95
DIMENSIONS						
Overall Length						301
Deck Length						267
Deck Width						98.5
Deck Height					22	23
	8.5 x 24	8.5 x 24	8.5 x 28	8.5 x 28		
Model #	H10124FTCHV-140	H10124FTCHV-100	H10128FTCHV-140	H10128FTCHV-100		
CAPACITIES						
GVWR (lbs)	14000	9900	14000	9900		
GAWR (lbs/axle)	7000	5200	7000	5200		
Curb Weight	4240	3620	4150	3950		
Payload	9760	6280	9850	5950		
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" x 2" Steel Triple Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Coupler	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock	2-5/16" Adjustable	2-5/16" A-Frame, Posi-Lock		
Deck Width	98.5					
Deck Length	315			363		
Deck Height	23	22	23	22		
Tongue Jack	7K Drop Leg, Set-Back	2K Coupler Mounted	7K Drop Leg, Set-Back	2K Coupler Mounted		
Wall Studs	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center	Steel Tube, 16" On-Center	Steel Tube, 24" On-Center		
Roof Bows	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center	Galvanized Steel Tube, 16" On-Center	Galvanized Steel Tube, 24" On-Center		
Front Profile	V-Nose					
Dovetail	4' Interior					
Ramp(s)	4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Fenders	Teardrop Smooth Aluminum					
Axle	(2) 7000 lb. Drop Spring Brake	(2) 5200 lb. Drop Spring Brake	(2) 7000 lb. Drop Spring Brake	(2) 5200 lb. Drop Spring Brake		
Hubs	Easy Lube					
Tires	ST235/80R16E 10-PR	ST225/75R15D 8-PR	ST235/80R16E 10-PR	ST225/75R15D 8-PR		
Wheels	16", 8-Hole Steel	15", 6-Hole Steel	16", 8-Hole Steel	15", 6-Hole Steel		
Exterior Finish	.030" Aluminum					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Exterior Fastening	VHB Bonded (Screwless)					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Warranty	Limited 3-Year Warranty					
Length Interior Box	315			363		
Height Overall	99	98	99	98		
Height Interior	73.5					
Height Rear Opening	68					
Width Interior	98.5					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

	8.5 x 24	8.5 x 24	8.5 x 28	8.5 x 28
Width Between Fender			82	
Width Rear Opening			95	
DIMENSIONS				
Overall Length		349		397
Deck Length		315		363
Deck Width			98.5	
Deck Height	23		22	
			23	22

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.