



SPECIFICATIONS -MIDSOTA TILTS (NEW)

MIDSOTA TBWB 17.6K

	102 x 24	102 x 26	102 x 28	102 x 30
Model #	N-TBWB24-176	N-TBWB26-176	N-TBWB28-176	N-TBWB30-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4760	5010	5160	5543
Payload	12840	12590	12440	12057
CHASSIS				
Frame	8" x 3" Steel Tube			
Crossmembers	3" Steel Channel, 16" On-Center			
Coupler	2 5/16" Adjustable Channel Mount, Demco EZ Latch			
Coupler Height	11.5 - 19.5			
Deck Height	28			
Tongue Jack	12K Drop Leg, Set-Back			
Fenders	Square Rolled Steel Tread Plate			
Axle	(2) 8000 lb. Slipper Spring Brake			
Tires	215/75R17.5J 18-PR			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine			
Tie Downs	Stake Pockets and Rub Rail			
Wiring	No Exposed Wiring			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	Hydraulic Lock			
Width Between Fender	82			
Load Angle	12			
DIMENSIONS				
Overall Length	346	370	394	418
Deck Height	28			
Coupler Height	11.5 - 19.5			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA TILTS (NEW)
MIDSOTA TBWB 22K

	102 x 22	102 x 24	102 x 30	102 x 32
Model #	N-TBWB22-220	N-TBWB24-220	N-TBWB30-220	N-TBWB32-220
CAPACITIES				
GVWR (lbs)	22000			
GAWR (lbs/axle)	10000			
Curb Weight	4875	4860	5500	5560
Payload	17125	17140	16500	16440
CHASSIS				
Frame	8" x 3" Steel Tube			
Crossmembers	3" Steel Channel, 16" On-Center			
Coupler	2-5/16" 4-Bolt Flat Plate			
Coupler Height	0			
Tongue Jack	12K Drop Leg, Set-Back			
Fenders	Square Rolled Steel Tread Plate			
Axle	(2) 10000 lb. Torsion Brake			
Tires	ST235/75R17.15J 18-PR			
Exterior Finish	Industrial Grade Polymer Finish			
Decking	2" Pressure Treated Pine			
Tie Downs	Stake Pockets and Rub Rail			
Wiring	No Exposed Wiring			
Exterior Lights	Full LED, DOT Compliant			
Hydraulic Components	Hydraulic Lock			
DIMENSIONS				
Coupler Height	0			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA TILTS (NEW)
MIDSOTA TBWB GN 16.1K

	102 x 22	102 x 24	102 x 26	102 x 26	102 x 28	102 x 32
Model #	N-TBWB22-184G	N-TBWB24-184G	N-TBWB26-184G	N-TBWB26-241G	N-TBWB28-184G	N-TBWB32-184G
CAPACITIES						
GVWR (lbs)	18400			24100	18400	
GAWR (lbs/axle)	8000			7000	8000	
Curb Weight	5110	5360	5610	5750	5760	6574
Payload	13290	13040	12790	18350	12640	11826
CHASSIS						
Frame	8" x 3" Steel Tube					
Crossmembers	3" Steel Channel, 16" On-Center					
Coupler	2-5/16" Adjustable Gooseneck					
Coupler Height	0					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Fenders	Square Rolled Steel Tread Plate					
Axle	(2) 8000 lb. Slipper Spring Brake			(3) 7000 lb. Slipper Spring Brake	(2) 8000 lb. Slipper Spring Brake	
Tires	215/75R17.5J 18-PR			ST235/80R16E 10-PR	215/75R17.5J 18-PR	
Exterior Finish	Industrial Grade Polymer Finish					
Decking	2" Pressure Treated Pine					
Tie Downs	Stake Pockets and Rub Rail					
Exterior Storage	Receiver Tube Winch Mount, Spare Tire Carrier					Spare Tire Carrier
Wiring	No Exposed Wiring					
Exterior Lights	Full LED, DOT Compliant					
Hydraulic Components	Hydraulic Lock					
DIMENSIONS						
Coupler Height	0					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.



SPECIFICATIONS -MIDSOTA TILTS (NEW)
MIDSOTA TBWB GN 23K

	102 x 22	102 x 26	102 x 28
Model #	N-TBWB22-230G	N-TBWB26-230G	N-TBWB28-230G
CAPACITIES			
GVWR (lbs)		23000	
GAWR (lbs/axle)		10000	
Curb Weight	5950	5710	5860
Payload	17050	17290	17140
CHASSIS			
Frame	8" x 3" Steel Tube		
Crossmembers	3" Steel Channel, 16" On-Center		
Coupler	2-5/16" Adjustable Gooseneck		
Coupler Height	0		
Tongue Jack	Dual 12K, 2-Speed Landing Gear		
Fenders	Square Rolled Steel Tread Plate		
Axle	(2) 10000 lb. Torsion Brake		
Tires	ST235/75R17.15J 18-PR		
Exterior Finish	Industrial Grade Polymer Finish		
Decking	2" Pressure Treated Pine		
Tie Downs	Stake Pockets and Rub Rail		
Exterior Storage	Receiver Tube Winch Mount, Spare Tire Carrier		
Wiring	No Exposed Wiring		
Exterior Lights	Full LED, DOT Compliant		
Hydraulic Components	Hydraulic Lock		
DIMENSIONS			
Coupler Height	0		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.